

MEDIUM FLOW RATE FLOMETER TYPE R

CHARACTERISTIC

- Employment: liquids or Gases
- Accuracy: $\pm 5\%$ of f.s.
- Max working pressure: 10 bar
- Max working temperature: 70°C
- Connections: PVC, AISI 304 or AISI 316

ACCESSORIES

- Proxy FP/1 o FP/3 for Min or Max flow alarm or both
- Reinforced versions PN 40 e PN 64
- versions with opposite connections



TYPE	Standard flowrate		Threaded connections				Flanged connections										
	WATER	AIR	DN	A	B	C	DN	A	B	C							
	Lt/h	Nmc/h															
R-1	120	6	1/2"	127	35	40	15	127	60	35							
	200	8															
	300	10															
	400	12															
	500																
R-2	600	15	1/2"	160	40	45	20	160	80	40							
	800		3/4"														
	1200		1"								190	40	50	25	190	80	45
	1500																
	2000																
R/3	3000	40	1"	190	40	50	25	190	80	45							
R/4	6000	60	1"	190	40	60	40	190	80	60							
	8000		1"1/4														
	12000		1"1/2														

TIPO	SQUARE CONNECTION					
	DN	A	B	C	E	I
R/1	3/8" - 1/2"	127	15	40	40	95
R/2	1/2" - 3/4" - 1"	160	15	45	45	115
R/3	3/4" - 1"	190	15	50	50	125
R/4	1" - 1"1/4 - 1"1/2	238	16	60	40	165

The rates are indicative, it's possible to supply different scale for specific needfull.

Standard flow rates for water 20 °C and AIR @ at atmospheric pressure

