

FLOWMETER FOR MEDIUM FLOWRATE TYPE RR / PLR

CHARACTERISTICS

- Employments: clean liquids or gases
- Precision: $\pm 5\%$ fs.
- Maximum working pressure: 10 bar
- Maximum working temperature: 70°C
- Connections and Flow regulator: Brass, AISI 304, AISI 316
- input flow regulator

ACCESSORIES

- Inductive Proxy PNP, FP/1 or FP/3 for min and max flow alarm
- output flow regulator



Standard rates for water 20°C or Air at atmospheric pressure

| TYPE | Standard Flowrate | | Threads Connection | | | |
|-------|-------------------|-------|--------------------|-----|-----|----|
| | WATER | AIR | | | | |
| | L/h | Nm3/h | G | L | I | C |
| R-1/R | 120 | 6 | | | | |
| | 200 | | | | | |
| | 300 | 8 | 3/8" - 1/2" | 160 | 115 | 40 |
| | 400 | | | | | |
| | 500 | 10 | | | | |
| R-2/R | 600 | | | | | |
| | 800 | 15 | | | | |
| | 1200 | | 3/8" - 1/2" | 190 | 140 | 45 |
| | 1500 | 25 | | | | |
| | 2000 | | | | | |

| TYPE | Standard flowrate | | Threads Connection | | | |
|--------|-------------------|-------|--------------------|-----|-----|----|
| | WATER | AIR | | | | |
| | L/h | Nm3/h | G | L | I | C |
| PL-1/R | 120 | 6 | | | | |
| | 200 | | | | | |
| | 300 | 8 | 3/8" - 1/2" | 215 | 170 | 40 |
| | 400 | | | | | |
| | 500 | 10 | | | | |
| PL-2/R | 600 | | | | | |
| | 800 | 15 | | | | |
| | 1200 | | 3/8" - 1/2" | 255 | 205 | 45 |
| | 1500 | 25 | | | | |
| | 2000 | | | | | |

The rates are indicative, it's possible to supply different scale for specific needful

