

# MEDIUM FLOW RATE FLOMETER TYPE PL

## CHARACTERISTICS

- Employment: Liquids or Gas
- Accuracy:  $\pm 5\%$  del f.s.
- Max working pressure: 10 bar
- Max working temperature: 70°C
- Connections: PVC, AISI 304 or AISI 316

## ACCESSORIES

- Proxy FP/1 or FP/3 for Min or Max flow alarm



Standard rates for water 20°C or Air at atmospheric pressure

TYPE	Standard flowrate		threaded connection			flanged connection				
	WATER	AIR	DN	A	B	C	DN	A	B	C
	L/h	Nmc/h								
PL/1	200	6	1/2"	180	35	40	15	180	60	35
	400	8								
	600	10								
PL/2	800	15	1/2"	220	40	45	15	220	80	40
	1200	25	3/4"				20			
	2000		1"				25			
PL/3	4000	40	1"	260	40	50	25	260	80	45
PL/4	6000	60	1"1/2	260	40	60	40	260	80	60
PL/5	12000	100	1"1/2	260	40	75	40	260	80	75
	15000		2"				50			
	20000		2"1/2				65			
	30000		2"1/2				65			

TYPE	SQUARE CONNECTION					
	DN	A	B	C	E	I
PL/1	3/8" - 1/2"	180	15	40	35	145
PL/2	1/2" - 3/4" - 1"	220	15	45	35	175
PL/3	3/4" - 1"	260	15	50	40	195
PL/4	1" - 1"1/4 - 1"1/2	260	15	60	40	195
PL/5	1"1/2 - 2" - 2"1/2	260	82,5	75	45	350

The rates are indicative, it's possible to supply different scale for specific needfull.

