

FLOWMETER TYPE MK

CHARACTERISTICS

- Applications: Liquids and Gas
- Accuracy: $\pm 5\%$ del f.s.
- Max. working pressure: 10 bar
- Max. working temperature: 70°C (on request Max 100°C)
- Structure: antacid PVC (on request polypropylene)
- Float: AISI 316 (on request PVC, PTFE etc.)

ACCESSORIES

- Min/Max flow indicator
- polypropylene structure for max. temperature up to 100°C



Standard rates for water 20°C or Air at atmospheric pressure

TYPE	WATER L/h	AIR NM ³ /h	Threaded Connections DN	A	B
MKF	320	6	1/2"	430	80
	420	8	3/4"		
	600	10	1"		
	800				
MKE	1200	20	3/4"	430	80
	1500		1"		
MKD/4	2000	40	3/4"	430	100
	2500		1"		
	3500				
MKD/5	4000	60	1"	430	100
	5000		1"1/4"		
	6000		1"1/2"		
MKC	5000	80	1"	540	100
	6000		1"1/4"		
	8000		1"1/2"		
MKB	10000	130	1"1/2"	540	120
	12500		2"		
	15000				
MKA	20000	160	2"	540	140
	25000		2"		
	30000		2"1/2"		
	37000		3"		
	45000				

